

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>G06K 7/00, 13/08</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/07136</b> (43) International Publication Date: 10 February 2000 (10.02.00)
(21) International Application Number: <b>PCT/EP99/05404</b> (22) International Filing Date: <b>28 July 1999 (28.07.99)</b> (30) Priority Data: <b>98/09710 29 July 1998 (29.07.98) FR</b> (71) Applicant (for all designated States except US): <b>FRAM-ATOME CONNECTORS INTERNATIONAL [FR/FR];</b> <b>Tour Framatome, 1 Place de la Coupole, F-92400</b> <b>Courbevoie (FR).</b> (72) Inventor; and (75) Inventor/Applicant (for US only): <b>PERNET, Michel [FR/FR];</b> <b>8, Grande Rue, F-25300 Doubs (FR).</b> (74) Agent: <b>BEETZ &amp; PARTNER; Steinsdorfstrasse 10, D-80538</b> <b>München (DE).</b>	(81) Designated States: <b>CA, CN, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b>  <b>Published</b> <i>With international search report.</i>	

(54) Title: **LOCKABLE SMART-CARD CONNECTOR**

## (57) Abstract

The invention relates to a lockable connector (1) for a smart-card (2), which includes a movable carriage (6) intended to bring the smart-card (2) from a first position, in which the said card (2) projects to the outside of the connector (1), into a second position, in which the said card (2) is immobilized inside the said connector (1) in order to be read. According to the invention, the said connector (1) includes a lever (5) which is mounted so as to pivot about a pin (7) and has a first end (8) extending near the inlet (10) of the connector (1) and a second end (12) extending towards the inside of the connector (1) and in that the said carriage (6) includes at least one arm (14) which, on the one hand, laterally pushes back the said first end (8) of the pivoting lever (5) in order to allow the smart-card (2) to be inserted into the connector (1) when the carriage (6) is in the first position and, on the other hand, laterally pushes back the second end (12) of the pivoting lever (5) when the carriage (6) is in the second position in such a way that the first end (8) of the lever (5) at least partially closes off the inlet of the said connector (1).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

### LOCKABLE SMART-CARD CONNECTOR

The present invention relates to a lockable smart-card connector operating according to the landing-type technology.

The invention relates more particularly to a connector which includes a movable carriage intended to bring the smart-card from a first position, in which the said card partially projects to the outside of the connector, into a second position, in which the said card is immobilized inside the said connector in order to be read.

In applications using smart-cards, it is important to be certain that the card is inserted correctly and remains in the position which allows nominal operation of its microcircuit. For this purpose, the movable carriage carrying the smart-card has to be positioned correctly.

The prior art, especially German Patent Application DE-195 21 360, teaches a locking system which allows the carriage carrying the card to be immobilized in the desired position. Such a system consists of a lever which must be pushed manually once the card is inserted into the reader, the said card being pushed right into the required position.

A drawback of this system stems from the fact that it requires manual intervention by the user in order to insert the smart-card into the connector and also to withdraw it therefrom.

One objective of the invention is to produce a connector in which the smart-card is positioned and locked in the connector, as well as unlocked and ejected, in an automatic manner without intervention by the user.

Another objective of the invention is to prevent a second card from being inserted in error into the connector.

In order to achieve these objectives, the connector according to the invention is characterized in that it includes a lever which is mounted so as to

- 2 -

pivot about a pin and has a first end extending near the inlet of the connector and a second end extending towards the inside of the connector and in that the said movable carriage includes at least one arm which, on the one hand, laterally pushes back the said first end of the pivoting lever in order to allow the smart-card to be inserted into the connector when the carriage is in the first position, and on the other hand, laterally pushes back the second end of the pivoting lever when the carriage is in the second position in such a way that the first end of the lever at least partially closes off the inlet of the said connector.

With such a system, it is therefore no longer necessary to manually actuate a lever in order to lock the smart-card in the read position. Furthermore, the fact that the first end of the lever at least partially closes off the inlet of the said connector prevents a second card from being inserted in error into the connector.

Other features and advantages of the invention will emerge from the description which follows, taken by way of non-limiting example, with reference to the appended figures in which:

- Figure 1 shows a top view of a connector according to the invention;

- Figure 2 shows a perspective view of the connector of Figure 1 into which a smart-card (an unlocked card) has been partially inserted and of a cover intended for covering this connector;

- Figure 3 shows a perspective view of the connector of Figure 1 in which a smart-card (a locked card) has been fully inserted and of a cover intended for covering this connector.

Figures 1, 2 and 3 show views of a lockable connector 1 for a smart card 2, which includes an insulating support 4 on which a carriage 6 is movably mounted, the said carriage 6 being intended to bring the smart-card 2 from a first position, for example

- 3 -

that shown in Figure 2, in which the card 2 projects to the outside of the connector 1, into a second position, shown in Figure 3, in which the said card 2 is immobilized inside the said connector 1 in order to be read.

At the moment when the card is inserted into the connector, the movable carriage 6 lies to the rear in a first position, thus held in place by means of a return spring (not shown).

As may be seen in these Figures 1, 2 and 3, the connector 1 includes a lever 5 which is mounted so as to pivot about a pin 7 and has a first end 8 extending near the inlet 10, the said first end 8 being slightly curved in the direction of this inlet 10, and a second end 12 extending towards the inside of the connector 1. The carriage includes an arm 14, which, when the carriage 6 is in the first position shown in Figure 2, laterally pushes back the first end 8 of the pivoting lever 5 in order to allow the smart-card 2 to be inserted into the connector 1. When the card 2 comes into abutment at the front of the movable carriage 6, said card, continuing to be pushed forwards, entrains in its movement the said carriage 6. At the end of travel, this movement consequently means that the arm 14 laterally pushes back the second end 12 of the lever 5, thus making the said lever 5 pivot about the pin 7. In this way, the first end 8 at least partially closes off the inlet 10 of the said connector 1, as shown in Figure 3.

According to a preferred embodiment of the invention, the arm 14 of the carriage 6 has projection 20 which exerts a thrust on the first end 8 (or alternatively the second end 12) of the lever 5 when the carriage 6 is in the first position shown in Figure 2 (or alternatively in the second position shown in Figure 3). Preferably, each of the ends 8, 12 of the lever 5 has at least one inclined plane 22 which interacts with the projection 20 of the arm 14 of the carriage 6 in order to make the said lever 5 pivot

- 4 -

about the pin 7. Furthermore, the connector 1 includes a locking system 30 intended to immobilize the said carriage 6 in the position for reading the card 2. The said locking system preferably includes a first hook 32, integral with the carriage 6, which locks onto a second hook 34 which is mounted so as to pivot on a pivot pin 36 arranged at the bottom of the connector 1 and which possesses, in the example shown, a finger 37 operable from the outside. It may be noted here that this action can also be carried out internally by means of an electromagnet.

The card 2 is unlocked by making the second hook 34 pivot, in this case by means of the external finger 37, this second hook 34 releasing the first hook 32 on the carriage 6. The latter is then automatically pushed back towards the outside of the connector 1 under the action of the return spring (not shown). When the carriage 6 is pushed back far enough to the outside of the connector 1, the projection 20 laterally pushes back the first end 8 of the lever 5 again, thus causing the said lever 5 to pivot about the pin 7.

The end 8, by being moved laterally, allows the card 2 to leave the connector 1.

- 5 -

## CLAIMS

1. Lockable connector (1) for a smart-card (2), which includes a movable carriage (6) intended to bring the smart-card (2) from a first position, in which the said card (2) projects to the outside of the connector (1), into a second position, in which the said card (2) is immobilized inside the said connector (1) in order to be read, characterized in that the said connector (1) includes a lever (5) which is mounted so as to pivot about a pin (7) and has a first end (8) extending near the inlet (10) of the connector (1) and a second end (12) extending towards the inside of the connector (1), and in that the said carriage (6) includes at least one arm (14) which, on the one hand, laterally pushes back the said first end (8) of the pivoting lever (5) in order to allow the smart-card (2) to be inserted into the connector (1) when the carriage is in the first position and, on the other hand, laterally pushes back the second end (12) of the pivoting lever (5) when the carriage (6) is in the second position in such a way that the first end (8) of the lever (5) at least partially closes off the inlet (10) of the said connector (1).

2. Connector according to Claim 1, characterized in that the arm (14) of the carriage (6) has at least one projection (20) which exerts a thrust on the first end (8) (or alternatively the second end (12)) of the lever (5) when the carriage (6) is in the first position (or alternatively in the second position).

3. Connector (1) according to Claim 1, characterized in that each of the ends (8, 12) of the lever (5) has at least one inclined plane (22) which interacts with the projection (20) of the arm (14) of the carriage (6) in order to make the said lever (5) pivot about the pin (7).

4. Connector (1) according to one of Claims 1 to 3, characterized in that it furthermore includes a locking system (30) intended to immobilize the said

- 6 -

carriage (6) in the said read position.

5. Connector according to Claim 4, characterized in that the said locking system (30) includes a first hook (32), integral with the carriage (6), which locks onto a second hook (34) mounted so as to pivot on a pivot pin (36) arranged at the bottom of the connector (1) when the smart-card (2) comes into the read position.

6. Connector according to Claim 5, characterized in that the card (2) is unlocked by making the second hook (34) pivot, releasing the first hook (32) on the carriage (6) which is then automatically pushed back towards the outside of the connector (1) under the action of a return spring.



1/3




Fig. 1

2/3




Fig. 2



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/05404

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 G06K7/00 G06K13/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 749 088 A (FRAMATOME CONNECTORS INT) 18 December 1996 (1996-12-18) column 2, line 52 -column 4, line 1; figures 1,2	1-4
A	DE 196 45 460 A (THOMAS & BETTS GMBH) 7 May 1998 (1998-05-07) column 1, line 59 -column 3, line 62; figures 1-5	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

13 October 1999

Date of mailing of the international search report

20/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Degraeve, A

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International Application No

PCT/EP 99/05404

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0749088 A	18-12-1996	FR 2735599 A	20-12-1996
DE 19645460 A	07-05-1998	CA 2242462 A	14-05-1998
		WO 9820441 A	14-05-1998
		EP 0877988 A	18-11-1998